

CHLOROFOAM

Description

Chlorofoam is a sodium hydroxide and sodium hypochlorite based foaming detergent. The foam generated allows for longer contact time on surfaces, while the high alkalinity and chlorination provides an excellent cleaning performance. Ideal for cleaning drains, floors, walls and the outside of stainless steel vessels.

Benefits

- Easily dissolves organic soil
- Suitable for all water hardness's
- Provides an easy way to clean hard to reach areas

Application and rates of use

Chlorofoam is ideally applied through a Techni-Foamer available to purchase separately from Sky Agro Ltd. Use at 3-5% v/v at ambient temperatures to a maximum of 50°C. For foam cleaning, remove loose debris and pre rinse with water. Apply the Chlorofoam and leave for about 20 minutes before being rinsed away with water. For heavier soiled surfaces, gentle scrubbing before rinsing may be necessary. Temperatures above 50°C should be avoided as the rate of chlorine loss will be accelerated markedly. Ensure stainless steel surfaces are properly rinsed before the foam has dried out, this will avoid streaking marks and possible corrosion.

Storage and shelf life

- Store out of extreme temperatures and away from direct sunlight
- Keep in original container
- Keep containers sealed when not in use
- Use within 12 months of manufacture

PRODUCT CODE

7361

PACKAGING

25 Litres, 200 Litres

STORAGE

Store in original container.

Keep away from Chlorines and flammables.

Recommended storage temperature below 25 degrees C.

Store away from direct sunlight.

Do not allow to freeze.

SHELF LIFE

Use within 12 months from the date of manufacture.

REVISION NUMBER 001
REVISION DATE 10/02/2026

SKY AGRO LTD

Unit C, West March Industrial Estate, Daventry, Northampton, NN11 4SA

info@sky-agro.com

T: 01327 828001